

## HETHON FEEDER PARTLIST 61-FS-GE

| Pos. | Drw-Number     | Description   | Material             | Wearing parts | Qty |
|------|----------------|---|----------------------|---------------|-----|
| 1    | 60/70-001-15   | FRAME   | AISI304              |               | 1   |
| 2    | 60/70-512-20   | GEARED MOTOR 0,37 kW 3f 50Hz 230/400 V                    |                      |               | 1   |
| 3    | 60/70-500-01   | PADDLE BEARING HOLDER front                               | AISI304              |               | 2   |
| 4    | 60/70-505-00   | PLAIN BEARING (Paddle front/back)                         | Tin Bearing Bronze   | X             | 4   |
| 5    | 60/70-004-01 R | PADDLE RIGHT  | AISI304              |               | 1   |
| 6    | 60/70-004-01 L | PADDLE LEFT   | AISI304              |               | 1   |
| 7    | 60/70-004-05   | PADDLE BLOCK RING   | AISI304              |               | 2   |
| 8    | 60/70-010-01   | FORK  | S235JR               |               | 2   |
| 9    | 60/80-010-02   | GUIDE ON FORK   | POM Acetal Copolymer | X             | 4   |
| 10   | 60/70-505-06   | DISTANCE WASHER FORK - 2mm Left side                      | POM Acetal Copolymer | X             |     |
| 11   | 60/70-505-05   | DISTANCE WASHER FORK - 5mm Right side                     | POM Acetal Copolymer | X             | 1   |
| 12   | 60/70-010-05   | BREAK PIN - DIN 1481 6 x 50                               |                      |               | 2   |
| 13   | 60/70-501-00   | BALL BEARING for main drive shaft front                   |                      | X             | 1   |
| 14   | 60/70-502-00   | BALL BEARING for main drive shaft back and excenter shaft |                      | X             | 3   |
| 15   | 60/70-018-00   | EXCENTER assembly   |                      |               | 1   |
| 16   | 60/70-007-00   | MAIN DRIVE SHAFT assembly                                 | AISI304              |               | 1   |
| 17   | 60/70-007-02   | KEY 5 x 5 x 20  |                      |               | 1   |
| 18   | 60/70-017-00   | DISTANCE BUSH main drive shaft                            | AISI304              |               | 1   |
| 19   | 60/70-513-18S  | SPROCKET T18 Motor  | AISI304              | X             | 1   |
| 20   | 60/70-514-15S  | SPROCKET T15 Main drive shaft                             | AISI304              | X             | 1   |
| 21   | 60/70-515-18S  | SPROCKET T18 Excenter                                     | AISI304              | X             | 1   |
| 22   | 60/70-516-12S  | SPROCKET T12 Chain tensioner                              | AISI304              | X             | 1   |
| 23   | 60/70-021-00   | BOLT CHAIN TENSIONER (012.9 SC SHLDSCR H8 (M8)10X40)      | AISI304              | X             | 1   |
| 24   | 60/70-532-00   | PLAIN BEARING for sprocket chain tensioner                | Tin Bearing Bronze   | X             | 1   |
| 25   | 40/70-021-03   | WASHER for bolt chain tensioner                           | AISI304              |               | 1   |
| 26   | 40/70-022-01   | GUIDE NUT DIN 508 M8 for bolt for sprocket                | AISI304              |               | 1   |
| 27   | 60/70-009-02   | BEARING SUPPORT   | AISI304              |               | 1   |
| 28   | 60/70-023-00   | FILL PLATE BEARING SUPPORT                                | AISI304              |               | 1   |
| 29   | 60/70-521-00   | BUSH BEARING SUPPORT                                      | AISI304              |               | 2   |
| 30   | 60/70-517-02   | CHAIN   | AISI304              | X             | 1   |
| 31   | 60/70-518-01   | CHAIN LOCK  | AISI304              | X             | 1   |
| 32   | 60-014-01      | HOPPER SUPPORT  | AISI304              |               | 1   |
| 33   | 60-013-01      | FRONT PANEL   | AISI304              |               | 1   |
| 34   | 40/80-511-23   | STARLOCK WASHER 12  | AISI304              |               | 8   |
| 35   | 60/70-511-50   | TURN LOCK assembly  |                      |               | 6   |
| 36   | 40/70-512-91   | CLIP  | POM Acetal Copolymer |               | 4   |
| 37   | 60/70-011-01   | SIDE PANEL  | AISI304              |               | 2   |
| 38   | 60/70-012-01   | BACK PANEL  | AISI304              |               | 1   |
| 39   | 60/70-511-18   | LOCK BUSH BACK PANEL                                      | AISI304              |               | 2   |
| 40   | 40/80-511-30   | O-RING For lock bolt back panel                           | Rubber               |               | 2   |
| 41   | 40/70-508-05   | FOOT  |                      |               | 4   |
| 42   | 60-510-00      | HOPPER (Standard)   |                      | X             | 1   |
| 42   | 60-510-10      | HOPPER (Food grade)                                       |                      | X             |     |
| 42   | 60-510-20      | HOPPER (Anti static)                                      |                      | X             |     |
| 42   | 60-510-30      | HOPPER (Chlorine resistant)                               |                      | X             |     |
| 43   | 40/70-006-00   | HOPPER SHAFT  | AISI316              | X             | 1   |
| 44   | 60-005-00      | HOPPER BEARING  | POM Acetal Copolymer | X             | 1   |
| 44   | 60-005-01      | HOPPER BEARING (Air flushed)                              | POM Acetal Copolymer | X             |     |
| 45   | 60/70-503-00   | SEAL (NBR)  | Rubber               | X             | 1   |
| 45   | 60/70-503-01   | SEAL (Viton)  | Rubber               | X             |     |
| 46   | 40/80-000-01   | TYPE PLATE  | AISI304              |               | 1   |
| 47   | 40/80-000-00   | NAME STICKER  | Sticker              |               | 2   |
| 48   | 40/80-000-02   | SAFTEY STICKER  | Sticker              |               | 1   |
| 49   | 60-506-01      | NOZZLE AND INNER CLAMP                                    | AISI304              |               | 2   |
| 50   | 40/70-512-90   | BLIND PLATE   | AISI304              |               | 1   |